


LSACT24 Accessory connector

Spring type (Push IN), 0.25 to 2.5 mm², Screw latch, 18 pin type

■Summary



★ Wire holding structure : Spring type (Push IN)

★ Wire size (Ferrule) : 0.25 to 2.5mm²

*Accessory connector rock

method

Flange

*Number of pins : 18

■Specifications

ITEM		SPECIFICATION	
Classification		18 pins type	
Connection Type		-	
Attachment position on the IOM Backplane		Available on both right side and left	
Tightening torque (to the IOM Backplane)		0.2 to 0.25 Nm (Recommendation)	
Number of pins		18	
Pitch		5.08 mm	
Wire holding structure		Spring type (Push IN)	
Screw size		-	
Tightening torque		-	
Power supply (IEC)		320 V	
Rated current (IEC)		12 A @ 20℃	
Dielectric strength		2.21 kV AC (Between neighbor pins)	
Wire size		Wire end ferrule with isolation cover 0.25 to 2.5 mm² (AWG 24 to AWG 14)	
		Flexible 0.2 to 2.5 mm (AWG 24 to AWG 14)	
Stripping length		10 mm	
Flamability class UL94		V-0	
Environmental conditions	Ambient temperature	(Operating) -5 to 85°C	(Storage) -40 to 70°C
	Ambient humidity	(Operating) Less than 95% RH (No condensation)	(Storage) Less than 95% RH (No condensation)
Weight		0.03 kg	
Dimensions		25.2 mm (D) x 15.0 mm (H) x 101.5 mm (W) (Except projection)	

About compliant module type:

For compliant modules of this product, please refer to "Compliant accessory connector list (CGS-S9902-E-XX)".




MOVE THE WORLD FORW>RD MITSUBISHI HEAVY INDUSTRIES


SL:1 ECT:N/A




LSACT24 Accessory connector

Spring type (Push IN), 0.25 to 2.5 mm², Screw latch, 18 pin type







When using, please read the instruction manual attached to the product carefully and use it properly.

This catalog may not be distributed or reproduced in whole or in part without permission.

Please be aware that due to product improvements and modifications, the product description in this catalog may differ in certain respects from the actual product.

DIASYS Netmation/DIASYS Netmation4S is a registered trademark of Mitsubishi Heavy Industries, Ltd.

The service names and product names of other companies described in this catalog are the trademarks or registered trademarks of each company.



MOVE THE WORLD FORW>RD MITSUBISHI HEAVY INDUSTRIES GROUP