

# RS232HUB Data Transfer Unit (DTU)

Data Transfer Unit (8ch)



ITEM	SPECIFICATION
Interface	RS-232C (D-sub 9P) × 1ch (For maintenance) 100Base Ethernet (RJ45) × 2ch RS-232C × 8ch (Amphenol 36p connector × 2ch) (For connection to VIM)
Status display	Red LED status display(8)
Environmental conditions	(Operating) Ambient temperature : 0 ~ 55°C Relative temperature : 0 ~ 95%RH (No condensation) (Storage) Ambient temperature : -25 ~ 55°C Relative temperature : 0 ~ 95%RH (No condensation)
Power supply	DC24V±10%
Dimensions	145mmW x 100mmH x 145mmD
Standard/Directive	RoHS

## ■ Outline

- \* Data transfer from RS - 232C to Ethernet

When using, please read the instruction manual attached to the product carefully and use it properly.

This catalog may not be distributed or reproduced in whole or in part without permission.

Please be aware that due to product improvements and modifications, the product description in this catalog may differ in certain respects from the actual product.

DIASYS Netmation/DIASYS Netmation4S is a registered trademark of Mitsubishi Hitachi Power Systems, Ltd.

The service names and product names of other companies described in this catalog are the trademarks or registered trademarks of each company.